





Available Finishes

2-Tone

Black

()

Silver

760A Power Amplifier

T he 760A is the first amplifier to be housed in the slim Evolution series chassis, making it unusually compact, yet very heavy. A dual-mono, class A/B design with balanced differential circuitry, it exhibits all the sonic hallmarks which MOON products are globally known for: an airy, detailed and open top end, transparent and 3-dimensional in the midrange, robust, powerful and authorative in the bass. In a nutshell, the 760A will amplify music with all the harmonic accuracy, richness and dimensionality of a live musical performance.

Specifications

Output Power at 4Ω	260W per channel	Gain	31dB
Output Power at 8Ω	130W per channel	THD (20Hz - 20kHz @ 1W)	0.015%
Output Power - Bridged mono at 8Ω	500W	THD (20Hz - 20kHz @ 130W)	0.04%
Input Sensitivity	900mV RMS	Intermodulation distortion	0.01%
Input Impedance	47,500Ω	Crosstalk @ 1kHz	-102 dB
Signal-to-noise Ratio	104dB @ full power	Frequency response (full range)	10Hz - 200kHz +0/-3dB
Shipping weight	45lb/20kg	Dimensions (width x height x depth)	18.75 x 4.0 x 18.1 in 47.6 x 10.2 x 46.0 cm

from feedback.



Our "no overall feedback" amplifier circuit design which

accurate musical reproduction with respect to tonality;

results in the following: real-time amplification; more

non-existent transient intermodulation distortion;

the elimination of common phase errors resulting

proprietary toroidal transformer design.

An oversized dual-mono power supply using a custom

"Class A" power output to 5 watts for greater efficiency.

Full unsolicited RS-232 bidirectional feedback and 12

 Self-diagnostic system that detects both over-heating and the presence of DC in the input signal.

Volt trigger input/output for remote operation.

simaudio.com