

Vincent

PRODUCT INFORMATION

SP-332

Stereo Hybrid Power amplifier

In line with the new hybrid pre-amplifier SA-32, we have also revised the power amplifier SP-331. The result is the SP-332. At first glance immediately recognizable - the new VU meters on the front panel. The color backlight and the status LEDs can be switched between red, blue, green and white using a sliding switch on the back.

Inside, two 6N16 tubes working in differential push-pull form the input stage, giving the sound signal a certain warmth and naturalness. In the transistor output stage there are 8 large transistors available for the final amplification. These generate 150 watts per channel at 8 ohms - enough power to effortlessly drive even critical speakers.



Vincent
German Brand since 1995

powerLine

PRODUCT INFORMATION

SP-332

Stereo Hybrid Power amplifier

In the power supply, a 500W toroidal transformer provides the necessary power. Elcos with a capacity of 80,000 μ F "buffer" them. Transferred to the sound creates a "dry", powerful and deep bass fundament. The stabilization of the voltage is handled by a 6N15 tube.

Symmetrical and asymmetrical connections are available for connecting a preamplifier.



SP-332



Connections

SPECIFICATIONS

Frequency Response:	20 Hz – 20 kHz \pm 0.5 dB 20 Hz – 50 kHz \pm 2 dB
Nominal Output Power 8 Ohm:	2 x 150 Watt
Nominal Output Power 4 Ohm:	2 x 250 Watt
T.H.D.:	< 0.1%
Input Sensitivity:	1.35 V
Signal-to-Noise:	> 91 dB
Input Impedance:	47 KOhm
Inputs:	1 x Stereo XLR, 1 x Stereo RCA, 1 x Power Control (3.5 mm jack)
Outputs:	4 x 2 Speaker terminals, 1 x Power Control (3.5 mm jack)
Tubes:	2 x 6N16, 1 x 6N15
Max. Power Consumption:	414 Watt
Weight:	21.1 kg
Color:	Black or Silver
Dimensions (W x H x D):	426 x 165 x 430 mm

Vincent
German Brand since 1995

powerLine

For further information, please contact Mr. Christian Fröhling.
Sintron Vertriebs GmbH, Südring 14, 76473 Iffezheim, Telephone: 07229-182950
e-mail: info@sintron.de, www.vincent-highend.de